Package: pmxcode (via r-universe)

October 26, 2026

Title Create Pharmacometric Models

Version 0.3.3

Description Provides a user interface to create or modify pharmacometric models for various modeling and simulation software platforms.

License MIT + file LICENSE

Imports bsicons, bslib, config (>= 0.3.1), dplyr, flextable, glue, golem (>= 0.3.3), htmltools, htmlwidgets, jsonlite, magrittr, markdown, officer, pillar, rclipboard, readr, rhandsontable, rlang, shiny (>= 1.7.1), shinyAce, shinyFiles, shinyjs, stats, tidyr, tools, utils, xfun

VignetteBuilder knitr

Suggests knitr (>= 1.28), rmarkdown (>= 2.2)

Encoding UTF-8

LazyData true

Depends shinyBS

URL https://github.com/sbihorel/pmxcode, https://sbihorel.github.io/pmxcode/

Config/roxygen2/version 8.1.0

Config/pak/sysreqs libcairo2-dev cmake libfontconfig1-dev libfreetype6-dev libfribidi-dev make libharfbuzz-dev libicu-dev libjpeg-dev libpng-dev libtiff-dev libuv1-dev libwebp-dev libxml2-dev libssl-dev libx11-dev zlib1g-dev

Repository https://sbihorel.r-universe.dev

Date/Publication 2026-09-26 12:02:04 UTC

RemoteUrl https://github.com/sbihorel/pmxcode

RemoteRef HEAD

RemoteSha 37be9a0efa684fb78851e3801f281143ecd89f78

Contents

run_app 2

Index 4

`run_app` *Run the Shiny Application*

Description

Run the Shiny Application

Usage

```
run_app(
  onStart = NULL,
  options = list(launch.browser = TRUE),
  enableBookmarking = NULL,
  uiPattern = "/",
  ...
)
```

Arguments

`onStart`	A function that will be called before the app is actually run. This is only needed for `shinyAppObj`, since in the `shinyAppDir` case, a `global.R` file can be used for this purpose.
`options`	Named options that should be passed to the `runApp` call (these can be any of the following: "port", "launch.browser", "host", "quiet", "display.mode" and "test.mode"). You can also specify `width` and `height` parameters which provide a hint to the embedding environment about the ideal height/width for the app.
`enableBookmarking`	Can be one of `"url"`, `"server"`, or `"disable"`. The default value, `NULL`, will respect the setting from any previous calls to `enableBookmarking()`. See `enableBookmarking()` for more information on bookmarking your app.
`uiPattern`	A regular expression that will be applied to each `GET` request to determine whether the `ui` should be used to handle the request. Note that the entire request path must match the regular expression in order for the match to be considered successful.
`...`	arguments to pass to golem_opts. See '?golem::get_golem_options' for more details.

Value

Starts the PMXcode Shiny application

Examples

```
## Not run:
if( interactive() ){
  pmxcode::run_app()
}

## End(Not run)
```

Index

enableBookmarking(), *2*

run_app, 2